

HIGH PERFORMANCE END MILLS

GS-MILL TWO FLUTE GS-MILL FOUR FLUTE

List No.9382 Two Flute



This end mill having sharp edge corner is suitable for high-speed and long life milling of workpiece materials from raw materials to hardened materials, and is used in grooving.

(Unit) : mm

Dia. of Mill	Shank Dia.	Length of Cut	Overall Length
0.5	3	1.25	38
1	3	2.5	38
1.5	3	3.75	38
2	3	5	38
2.5	3	6.25	38
3	3	7.5	38
4	4	11	45
5	6	13	50
6	6	13	50
8	8	19	60
10	10	22	70
12	12	26	75

1 per tube

Dia. of Mill (mm)		Tolerance (mm)
Above	Up to	
	3	0~-0.015
3		0~-0.020

List No.9384 Four Flute



This end mill having sharp edge corner is suitable for high-speed and long life milling of workpiece materials from raw materials to hardened materials, and is used in side milling.

(Unit) : mm

Dia. of Mill	Shank Dia.	Length of Cut	Overall Length
1	3	2.5	38
2	3	5	38
3	3	7.5	38
4	4	11	45
5	6	13	50
6	6	13	50
8	8	19	60
10	10	22	70
12	12	26	75

1 per tube

Dia. of Mill (mm)		Tolerance (mm)
Above	Up to	
	3	0~-0.015
3		0~-0.020